



TECHNICAL DATA:

MODEL		RID 360 B-SERIES	RID 360 B-SERIES S	RID 400 B-SERIES	RID 400 B-SERIES S	RID 450 B-SERIES	RID 450 B-SERIES S
Version		open skid	silent	open skid	silent	open skid	silent
Order number Generator		713748	713749	713711	713712	713713	713715
Order number Generator with ATS		-	-	-	-	-	-
Order number Generator external ATS		728318	728318	728318	728318	728319	728319
Nom. output P.R.P. (cos = 0,8)	kVA/kW	360 / 288		400 / 320		450 / 360	
Nom. total current (cos = 0,8)	A	520		578		650	
Voltage	V	230 / 400		230 / 400		230 / 400	
Frequency	Hz	50		50		50	
Dimensions (L x W x H)	mm	2850x1700x2210	3351x1740x2411	3050x1420x2168	4000x1940x2383	3050x1420x2168	4000x1940x2383
Weight	kg	3050	3700	3150	4370	3400	4550
Noise level	dB(A)	85	71	81	70,9	82	69
Fuel tank capacity	l	1000		1000		1000	
Engine	Doosan	DP126LB		P158LE		DP158LC	
Speed range	rpm	1500		1500		1500	
Speed governor		electrical		electrical		electrical	
Fuel		diesel		diesel		diesel	
Cooling system		Water + air		Water + air		Water + air	
Displacement	l	11		14,6		14,6	
Engine output	kW	327		363		408	
Starter	V	24		24		24	
Oil type (recommended)		RID 10W40		RID 10W40		RID 10W40	
Engine oil volume	l	21		28		22	
Fuel consumption load 100/75%	l/h	76,0 / 57,1		89,3 / 65,1		99,6 / 72,9	
Generator		synchronous		synchronous		synchronous	
Isolation type		H		H		H	
Protection class		IP 23		IP 23		IP 23	

OPTIONS (description - page 44)	ORDER NUMBER					
Coolant heater	715120	715120	715117	715117	715118	715118
Fuel filter / water separator	754045	754045	754042	754042	754043	754043
External fuel tank 720 / 1000 L	718000 / 718010	718000 / 718010	718000 / 718010	718000 / 718010	718000 / 718010	718000 / 718010
Automatic fuel refilling system	on request	on request	on request	on request	on request	on request
Battery charger	733339	733339	733339	733339	733339	733339
RID LTE Modem	on request	on request	on request	on request	on request	on request
RID overvoltage protection	734033	734033	734033	734033	734033	734033